




FEDERNDDES DRUCKSTÜCK

SPRING LOADED THRUST PIECE



250°C 1.0715


s	d2	F1 (N)	F2 (N)	l1	d1	€/1
0,4	1,5	3	4,5	7	M3	•
0,8	2,5	8,5	14	9	M4	•
0,9	3	8	14	12	M5	•
1	3,5	11	18	14	M6	•
1,5	4,5	18	31	16	M8	•
2	6	24	45	19	M10	•
2,5	8	26	49	22	M12	•
3,5	10	41	86	24	M16	•
4,5	12	56	111	30	M20	•

☒ 240137/d1



FEDERNDDES DRUCKSTÜCK MIT VERSTÄRKTER FEDER

SPRING LOADED THRUST PIECE WITH HIGHER SPRING FORCE



150°C 1.0718

s	d2	F1 (N)	F2 (N)	l1	d1	€/1
0,4	1,5	5	7	7	M3	•
0,8	2,5	12	22	9	M4	•
0,9	3	19	30	12	M5	•
1	3,5	28	40	14	M6	•
1,5	5	47	73	16	M8	•
2	6	66	100	19	M10	•
2,5	8	66	120	22	M12	•
3,5	10	90	180	24	M16	•
4,5	12	115	240	30	M20	•

☒ 240140/d1